# robern.

## Features

- Semi-recessed
- Mirrored doors and interior
- White exterior and interior finish
- 3-way adjustable concealed hinge system
- SAFESEAL™ gasket frame
- Rust-free aluminum construction
- Left or right hinge door available
- Electric feature includes two duplex 15 A, 110 VAC GFCI outlets
- Seven adjustable glass shelves
- Wire basket
- 26-1/8" (66.4 cm) x 73-3/8" (186.4 cm) x 11-1/8" (28.3 cm)

## **Codes/Standards Applicable**


Specified model meets or exceeds the following:

• Electrical options are UL listed for damp locations

Fairhaven™ sconce, brushed nickel

# FAIRHAVENTM CABINET

#### WITH ELECTRIC MFH1DCR8ER, ALSO MFH1DCR8EL, MFH1DBN8ER, MFH1DBN8EL



# **Specified Model**

**MLLWFHBN** 

Model	Description	
MFH1DCR8ER	Semi-recessed cabinet with chrome knob, right hinge with electric	
MFH1DCR8EL	Semi-recessed cabinet with chrome knob, left hinge with electric	
MFH1DBN8ER	Semi-recessed cabinet with brushed nickel knob, right hinge with electric	
MFH1DBN8EL	Semi-recessed cabinet with brushed nickel knob, left hinge with electric	
Optional Accessories		
MLLWFHCR	Fairhaven™ sconce, chrome	

# FAIRHAVENTM CABINET

# **Technical Information**

Roughing-in opening	18-1/2″ (47 cm) x 68-11/16″ (174.5 cm) x 4″ (10.2 cm)
Door opening angle	120°

## **Installation Notes**

Install this product according to the installation guide.

When determining the height of the mirrored cabinet, ensure the mirrored door will clear all obstacles, such as a faucet. A minimum clearance distance of 2" (5.1 cm) is required between the top of the faucet spout and the bottom of the cabinet crown molding and at least 1" (2.5 cm) clearance from the top of the cabinet crown molding to the ceiling.

Secure the screws (provided) to a stud to avoid possible property and product damage. If this is not possible, anchors (provided) must be inserted before installing the screws.

Cabinets project 7-1/8" (18.1 cm) from wall.

