

## EcoPower® Toilet Flushometer Valve, 1.6 gpf

### FEATURES

- Hydropower self-generating system
- Electronic flushometer valve complete with 1" angle stop and 1-1/2" vacuum breaker set
- 1.6 gpf or less
- Back spud floor, top spud and back spud wall models - concealed 4" x 4" Cover plate
- 24 hour automatic flush for trap seal protection

### MODELS

- TET3GN#SS  
Valve only, Surface mount, Satin finish
- TET3GN31#SS (1-1/2" Vacuum breaker)  
Back spud wall, Satin finish  
Complete set supplied with:  
Vacuum breaker & angle stop set - VB13RB-31 (Back spud wall)
  - 1" Angle stop - 10077t5
  - 1-1/2" Vacuum breaker - 10075t4
  - Outlet tube - TH559EDV176
  - Sweat solder kit - SJ3
- TET3GN32#SS (1-1/2" Vacuum breaker)  
Top spud, Satin finish  
Complete set supplied with:  
Vacuum breaker & angle stop set - VB9RB-32 (Top spud)
  - 1" Angle stop - 10077t5
  - 1-1/2" Vacuum breaker - 10075t3
  - Outlet tube - TH559EDV177
  - Sweat solder kit - SJ3
- TET3GN33#SS (1-1/2" Vacuum breaker)  
Back spud floor, Satin finish  
Complete set supplied with:  
Vacuum breaker & angle stop set - VB13RB-33 (Back spud floor)
  - 1" Angle stop - 10077t5
  - 1-1/2" Vacuum breaker - 10075t4
  - Outlet tube - TH559EDV175
  - Sweat solder kit - SJ3
- Optional Part:  
Z-4000-J - Adapter for ground joint angle stops

### COLORS/FINISHES

- #SS Stainless Steel Satin finish

### CODES/STANDARDS

- Meets or exceeds ASSE 1037, CSA B125.3
- Certifications: IAPMO(cUPC), ASSE, State of Massachusetts, City of Los Angeles, and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others
- ADA compliant



Piston Valve

### PRODUCT SPECIFICATION

TOTO® Model No. \_\_\_\_\_  
Automatic Infrared sensor activated, toilet valve. Heavy-duty 4" x 4" stainless steel coverplate with satin finish. Low water consumption of 1.6 gallons per flush. Piston valve with stainless steel self-cleaning debris screen and self-cleaning solenoid. Automatic flush every twenty four hours if not used. Electrical sensor separated from valve and sealed in a waterproof compartment. Manual override button incorporated. Through the use of TOTO's EcoPower® Flush Valves, using the valve 12 flushes per day will fully recharge the valve for up to 10 years.

