

Pressure Balancing Valve

FEATURES

- Corrosion resistant
- Anti-scald valve
- Adjustable temperature limit stop
- Tub port for use with diverter tub spout
- Integral shut-offs / check valves
- 1/2" NPT / sweat connections
- Back-to-back installation compatible without cross-over piping

CODES/STANDARDS

- Meets or exceeds ASME A112.18.1/CSA B125.1, ASSE 1016
- Certifications: IAPMO(cUPC), State of Massachusetts, City of Los Angeles, and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others



PRODUCT SPECIFICATION

Diaphragm pressure balancing valve shall have anti-scald protection and an adjustable temperature limit stop. Valve shall have tub port for use with diverter tub spout. Valve shall have integral shut-offs / check valve. Valve shall have 1/2" NPT / sweat connections. Valve model shall be TSPTM. Requires pressure balance trim. For optional tub spout a diverter valve and trim are needed for tub installations.

SPECIFICATIONS

- Warranty: Lifetime Limited Warranty (Residential Use)
One Year (Commercial Use)
- Material: Brass
- Shipping Weight: 2.6 lbs.
- Shipping Dimensions: 5" L x 5" W x 4-7/8" W

INSTALLATION NOTES

TRIM REQUIRED:
Pressure balance trim sold separately.

OPTIONAL TUB SPOUT:
Diverter valve and trim are needed for tub installations.

