TOTO®

CST453CUFG(R)

Drake® II 1G Close Coupled Toilet, 1.0GPF

FEATURES

- Tornado Flush™ system, low consumption (1.0GPF/3.8LPF)
- CeFiONtect™ ceramic glaze prevents debris, and mold from sticking to ceramic surfaces, leading to fewer chemicals and less water in cleaning.
- Universal Height
- Decorative two-piece design with high-profile tank
- Round front bowl and tank set, less seat
- Chrome trip lever
- 12" Rough-in, less supply

MODELS

- CST453CUFG
 With CeFiONtect ceramic glaze (#01)
- CST453CUFRG
 With right-hand trip lever, CeFiONtect ceramic glaze

COMPONENTS

- C453CUFG Round front bowl with CeFiONtect
- ST453U Tank and cover only
- ST453UR Tank and cover only, right-hand trip lever
- SS113 SoftClose® seat (sold separately)

COLORS/FINISHES

Standard #01 Cotton

PRODUCT SPECIFICATION

The Two-piece low consumption Tornado Flush system toilet shall be 1.0GPF/3.8LPF. Toilet shall have optional CeFiONtect ceramic glaze and be at Universal Height. Toilet shall have high-profile tank, round front bowl and Chrome trip lever. Toilet shall be TOTO Model CST453CUFG____.







CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO(cUPC), EPA Watersense, State of Massachusetts , City of Los Angeles, and others
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California AB715, California Green Building Code, City of Los Angeles Water Efficiency Ordinance
- BAA Buy American Act Compliant





Drake® II 1G Close Coupled Toilet, 1.0GPF

SPECIFICATIONS

Water Use
 Flush System
 Min. Water Pressure
 Water Surface
 Trap Diameter
 1.0GPF/3.8LPF
Tornado Flush™
 8 psi (static)
 6-7/8" x 8-7/8"
 2-1/8"

Trap Diameter 2-1/8"
 Rough-in 12"
 Trap Seal 2-1/8"

Warranty
 One Year Limited Warranty

Material Vitreous china

Shipping Weight C453CUFG 59.0lbs. ST453U(R) 31.5lbs.

Shipping Dimensions C453CUFG

27-1/2" L X 15-1/2" W1 X 11-1/4" W2 X 17-1/2" H

ST453U(R) 18" L X 9-1/2" W X 16-1/2" H

INSTALLATION NOTES

Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



