

12V LED 13W 10 Deg Spot 27K AZT

16009AZT27 (Textured Architectural Bronze)

Project Name: _____

Location: _____

Type: _____

Qty: _____

Comments: _____



Ordering Information

| | |
|--------------------|--------------------------------------|
| Product ID | 16009AZT27 |
| Finish | Textured Architectural Bronze |
| Available Finishes | AZT, AZT, BBR, BBR, BE, BE, BKT, BKT |

Dimensions

| | |
|--------|----------|
| Weight | 1.15 LBS |
|--------|----------|

Photometrics

| | |
|-----------------------|-------|
| Kelvin Temperature | 2700K |
| Color Rendering Index | 80 |

Specifications

| | |
|-------------------|----------------------|
| Material | Aluminum |
| Glass Description | 10 Beam Spread Optic |

Electrical

| | |
|-------------------------|--------------|
| Voltage | 12VAC/VDC |
| Operating Voltage Range | 9-15 VAC/VDC |

Qualifications

| | |
|--------------------|--|
| Safety Rated | Wet |
| Expected Life Span | 40000 Hours |
| Warranty | www.kichler.com/warranty |

Primary Lamping

| | |
|-----------------------|------------|
| Light Source | LED |
| Lamp Included | Integrated |
| Number of Lights/LEDs | 5 |
| Max or Nominal Watt | 13W |

Dimensions

| | |
|--------|-------|
| Height | 4.75" |
| Length | 4.75" |
| Width | 3.00" |

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

12V LED 13W 10 Deg Spot 30K AZT

16009AZT30 (Textured Architectural Bronze)

Project Name: _____

Location: _____

Type: _____

Qty: _____

Comments: _____



Dimensions

| | |
|--------|-------|
| Height | 4.75" |
| Length | 4.75" |
| Width | 3.00" |

Ordering Information

| | |
|--------------------|--------------------------------------|
| Product ID | 16009AZT30 |
| Finish | Textured Architectural Bronze |
| Available Finishes | AZT, AZT, BBR, BBR, BE, BE, BKT, BKT |

Dimensions

| | |
|--------|----------|
| Weight | 1.15 LBS |
|--------|----------|

Photometrics

| | |
|-----------------------|-------|
| Kelvin Temperature | 3000K |
| Color Rendering Index | 80 |

Specifications

| | |
|-------------------|----------------------|
| Material | Aluminum |
| Glass Description | 10 Beam Spread Optic |

Electrical

| | |
|-------------------------|--------------|
| Voltage | 12VAC/VDC |
| Operating Voltage Range | 9-15 VAC/VDC |

Qualifications

| | |
|--------------------|--|
| Safety Rated | Wet |
| Expected Life Span | 40000 Hours |
| Warranty | www.kichler.com/warranty |

Primary Lamping

| | |
|---------------------|------------|
| Light Source | LED |
| Lamp Included | Integrated |
| Max or Nominal Watt | 13W |

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

12V LED 13W 10 Deg Spot 27K BBR

16009BBR27 (Bronzed Brass)

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Ordering Information

| | |
|--------------------|--------------------------------------|
| Product ID | 16009BBR27 |
| Finish | Bronzed Brass |
| Available Finishes | AZT, AZT, BBR, BBR, BE, BE, BKT, BKT |

Dimensions

| | |
|--------|----------|
| Weight | 1.15 LBS |
|--------|----------|

Photometrics

| | |
|-----------------------|-------|
| Kelvin Temperature | 2700K |
| Color Rendering Index | 80 |

Specifications

| | |
|-------------------|----------------------|
| Material | Brass |
| Glass Description | 10 Beam Spread Optic |

Electrical

| | |
|-------------------------|--------------|
| Voltage | 12VAC/VDC |
| Operating Voltage Range | 9-15 VAC/VDC |

Qualifications

| | |
|--------------------|--|
| Safety Rated | Wet |
| Expected Life Span | 40000 Hours |
| Warranty | www.kichler.com/warranty |

Primary Lamping

| | |
|-----------------------|------------|
| Light Source | LED |
| Lamp Included | Integrated |
| Number of Lights/LEDs | 5 |
| Max or Nominal Watt | 13W |

Dimensions

| | |
|--------|-------|
| Height | 4.75" |
| Length | 4.75" |
| Width | 3.00" |

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

12V LED 13W 10 Deg Spot 30K BBR

16009BBR30 (Bronzed Brass)

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Ordering Information

| | |
|--------------------|--------------------------------------|
| Product ID | 16009BBR30 |
| Finish | Bronzed Brass |
| Available Finishes | AZT, AZT, BBR, BBR, BE, BE, BKT, BKT |

Dimensions

| | |
|--------|----------|
| Weight | 1.15 LBS |
|--------|----------|

Photometrics

| | |
|-----------------------|-------|
| Kelvin Temperature | 3000K |
| Color Rendering Index | 80 |

Specifications

| | |
|-------------------|----------------------|
| Material | Brass |
| Glass Description | 10 Beam Spread Optic |

Electrical

| | |
|-------------------------|--------------|
| Voltage | 12VAC/VDC |
| Operating Voltage Range | 9-15 VAC/VDC |

Qualifications

| | |
|--------------------|--|
| Safety Rated | Wet |
| Expected Life Span | 40000 Hours |
| Warranty | www.kichler.com/warranty |

Primary Lamping

| | |
|-----------------------|------------|
| Light Source | LED |
| Lamp Included | Integrated |
| Number of Lights/LEDs | 5 |
| Max or Nominal Watt | 13W |

Dimensions

| | |
|--------|-------|
| Height | 4.75" |
| Length | 4.75" |
| Width | 3.00" |

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

12V LED 13W 10 Deg Spot 27K BKT

16009BKT27 (Textured Black)

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Ordering Information

| | |
|--------------------|----------------------------------|
| Product ID | 16009BKT27 |
| Finish | Textured Black |
| Available Finishes | AZT, AZT, BBR, BBR, BE, BKT, BKT |

Dimensions

| | |
|--------|----------|
| Weight | 1.15 LBS |
|--------|----------|

Photometrics

| | |
|-----------------------|-------|
| Kelvin Temperature | 2700K |
| Color Rendering Index | 80 |

Specifications

| | |
|-------------------|----------------------|
| Material | Aluminum |
| Glass Description | 10 Beam Spread Optic |

Electrical

| | |
|-------------------------|--------------|
| Voltage | 12VAC/VDC |
| Operating Voltage Range | 9-15 VAC/VDC |

Qualifications

| | |
|--------------------|--|
| Safety Rated | Wet |
| Expected Life Span | 40000 Hours |
| Warranty | www.kichler.com/warranty |

Primary Lamping

| | |
|-----------------------|------------|
| Light Source | LED |
| Lamp Included | Integrated |
| Number of Lights/LEDs | 5 |
| Max or Nominal Watt | 13W |

Dimensions

| | |
|--------|-------|
| Height | 4.75" |
| Length | 4.75" |
| Width | 3.00" |

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

12V LED 13W 10 Deg Spot 30K BKT

16009BKT30 (Textured Black)

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Ordering Information

| | |
|--------------------|--------------------------------------|
| Product ID | 16009BKT30 |
| Finish | Textured Black |
| Available Finishes | AZT, AZT, BBR, BBR, BE, BE, BKT, BKT |

Dimensions

| | |
|--------|----------|
| Weight | 1.15 LBS |
|--------|----------|

Photometrics

| | |
|-----------------------|-------|
| Kelvin Temperature | 3000K |
| Color Rendering Index | 80 |

Specifications

| | |
|-------------------|----------------------|
| Material | Aluminum |
| Glass Description | 10 Beam Spread Optic |

Electrical

| | |
|-------------------------|--------------|
| Voltage | 12VAC/VDC |
| Operating Voltage Range | 9-15 VAC/VDC |

Qualifications

| | |
|--------------------|--|
| Safety Rated | Wet |
| Expected Life Span | 40000 Hours |
| Warranty | www.kichler.com/warranty |

Primary Lamping

| | |
|-----------------------|------------|
| Light Source | LED |
| Lamp Included | Integrated |
| Number of Lights/LEDs | 5 |
| Max or Nominal Watt | 13W |

Dimensions

| | |
|--------|-------|
| Height | 4.75" |
| Length | 4.75" |
| Width | 3.00" |

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.