12V LED 13W 35 Deg Flood 27K AZT

16010AZT27 (Textured Architectural Bronze)

Ondering Information	
Comments:	-
Qty:	-
Type:	-
Location:	_
Project Name:	_



Dimensions

Height	4.75"
Length	4.75"
Width	3.00"

O 1 1	
()rdering	Information
Ordering	miomiation

Product ID	16010AZT27
Finish	Textured Architectural Bronze
Available Finishes	AZT, AZT, BBR, BBR, BE, BE, BKT, BKT, WHT, WHT

Dimensions

Weight	1.15 LBS
--------	----------

Photometrics

Kelvin Temperature	2700K
Color Rendering Index	80

Specifications

Material	Aluminum
Glass Description	35 Beam Spread Optic

Electrical

Voltage	12VAC/VDC
Operating Voltage Range	9-15 VAC/VDC

Qualifications

Warrantv	www.kichler.com/warrantv
Expected Life Span	40000 Hours
Safety Rated	Wet

Light Source	LED
Lamp Included	Integrated
Number of Lights/LEDs	5
Max or Nominal Watt	13W

12 Volt 13W 35 Degree LED Accent Light 30K AZT

16010AZT30 (Textured Architectural Bronze)



Dimensions

Height	4.75"
Length	4.75"
Width	3.00"

Project Name: Location:
Type:
Qty:
Comments:

Ordering Information

Product ID	16010AZT30
Finish	Textured Architectural Bronze
Available Finishes	AZT, AZT, BBR, BBR, BE, BE, BKT, BKT, WHT, WHT

Dimensions

Weight	1.15 LBS
VVOIGITE	1.10 LDO

Photometrics

Kelvin Temperature	3000K	
Color Rendering Index	80	

Specifications

Material	Aluminum
Glass Description	35 Beam Spread Optic

Electrical

Voltage	12VAC/VDC
Operating Voltage Range	9-15 VAC/VDC

Qualifications

Warrantv www.kichler.com/warr	
Expected Life Span	40000 Hours
Safety Rated	Wet

Light Source	LED
Lamp Included	Integrated
Number of Lights/LEDs	5
Max or Nominal Watt	13W



12V LED 13W 35 Deg Flood 27K BBR

16010BBR27 (Bronzed Brass)

Project Name:
Location:
Туре:
Qty:
Comments:



Dimensions

Height	4.75"
Length	4.75"
Width	3.00"

Orc	lerin	a Inf	orm	ation
0.0		9	01111	atioi i

Product ID	16010BBR27	
Finish	Bronzed Brass	
Available Finishes	AZT, AZT, BBR, BBR, BE, BE, BKT, BKT, WHT, WHT	

Dimensions

Weight	1.15 LBS	
--------	----------	--

Photometrics

Kelvin Temperature	2700K
Color Rendering Index	80

Specifications

Material	Brass
Glass Description	35 Beam Spread Optic

Electrical

Voltage	12VAC/VDC
Operating Voltage Range	9-15 VAC/VDC

Qualifications

Safety Rated	Wet
Expected Life Span	40000 Hours
Warranty	www.kichler.com/warranty

Light Source	LED
Lamp Included	Integrated
Number of Lights/LEDs	5
Max or Nominal Watt	13W

12V LED 13W 35 Deg Flood 30K BBR

16010BBR30 (Bronzed Brass)

Ordering Inf	ormation	
Comments:		
Qty:		
Туре:		
Location:		
Project Name:		



Dimensions

Height	4.75"
Length	4.75"
Width	3.25"

Product ID	16010BBR30
Finish	Bronzed Brass
Available Finishes	AZT, AZT, BBR, BBR, BE, BKT, BKT, WHT, WHT

Dimensions

Weight	1.15 LBS	

Photometrics

Kelvin Temperature	3000K	_
Color Rendering Index	80	

Specifications

Material	Brass
Glass Description	35 Beam Spread Optic

Electrical

Voltage	12VAC/VDC
Operating Voltage Range	9-15 VAC/VDC

Qualifications

Safety Rated	Wet
Expected Life Span	40000 Hours
Warranty	www.kichler.com/warranty

Light Source	LED
Lamp Included	Integrated
Number of Lights/LEDs	5
Max or Nominal Watt	13W



12V LED 13W 35 Deg Flood 27K BKT

16010BKT27 (Textured Black)



Dimensions

Height	4.75"
Length	4.75"
Width	3.00"

Project Name:	_
ocation:	_
ype:	
Qty:	
Comments:	

Ordering Information

Product ID	16010BKT27
Finish	Textured Black
Available Finishes	AZT, AZT, BBR, BBR, BE, BE, BKT, BKT, WHT, WHT

Dimensions

Weight	1.15 LBS	

Photometrics

Kelvin Temperature	2700K	
Color Rendering Index	80	

Specifications

Material	Aluminum
Glass Description	35 Beam Spread Optic

Electrical

Voltage	12VAC/VDC
Operating Voltage Range	9-15 VAC/VDC

Qualifications

Safety Rated	Wet
Expected Life Span	40000 Hours
Warranty	www.kichler.com/warranty

Light Source	LED
Lamp Included	Integrated
Number of Lights/LEDs	5
Max or Nominal Watt	13W

12V LED 13W 35 Deg Flood 30K BKT

16010BKT30 (Textured Black)



Dimensions

Height	4.75"
Length	4.75"
Width	3.00"

Project Name:
Location:
Туре:
Qty:
Comments:

Ordering Information

Product ID	16010BKT30
Finish	Textured Black
Available Finishes	AZT, AZT, BBR, BBR, BE, BKT, BKT, WHT, WHT

Dimensions

Weight 1.15 LBS	Weight	1.15 LBS
-----------------	--------	----------

Photometrics

Kelvin Temperature	3000K	
Color Rendering Index	80	

Specifications

Material	Aluminum
Glass Description	35 Beam Spread Optic

Electrical

Voltage	12VAC/VDC
Operating Voltage Range	9-15 VAC/VDC

Qualifications

Warranty	www.kichler.com/warrantv
Expected Life Span	40000 Hours
Safety Rated	Wet

Light Source	LED
Lamp Included	Integrated
Number of Lights/LEDs	5
Max or Nominal Watt	13W

12V LED 13W 35 Deg Flood 27K WHT

16010WHT2

7077 00 B0g 1 1000 Z177 77111	Location:	
27 (Textured White)	Type:	
	Qty:	
	Comments:	
	Ordering Information	
	Product ID	16010WHT27
	Finish	Textured White
		A7T A7T DDD DDD DVT



Dimensions

Height	4.75"
Length	4.75"
Width	3.00"

Product ID	16010WHT27
Finish	Textured White
Available Finishes	AZT, AZT, BBR, BBR, BKT, BKT, WHT, WHT

Dimensions

Project Name: _

1.15 LBS

Photometrics

Kelvin Temperature	2700K	
Color Rendering Index	80	

Specifications

Material	Aluminum
Glass Description	35 Beam Spread Optic

Electrical

Voltage	12VAC/VDC
Operating Voltage Range	9-15 VAC/VDC

Qualifications

Safety Rated	Wet
Expected Life Span	40000 Hours
Warranty	www.kichler.com/warranty

Light Source	LED
Lamp Included	Integrated
Number of Lights/LEDs	5
Max or Nominal Watt	13W



12V LED 13W 35 Deg Flood 30K WHT

16010WHT30 (Textured White)



Dimensions

Height	4.75"
Length	4.75"
Width	3.00"

Project Name:	
Location:	
Туре:	
Qty:	
Comments:	

Ordering Information

Product ID	16010WHT30
Finish	Textured White
Available Finishes	AZT, AZT, BBR, BBR, BKT, BKT, WHT, WHT

Dimensions

Photometrics

Kelvin Temperature	3000K
Color Rendering Index	80

Specifications

Material	Aluminum
Glass Description	35 Beam Spread Optic

Electrical

Voltage	12VAC/VDC
Operating Voltage Range	9-15 VAC/VDC

Qualifications

Warranty	www.kichler.com/warrantv
Expected Life Span	40000 Hours
Safety Rated	Wet

Light Source	LED
Lamp Included	Integrated
Number of Lights/LEDs	5
Max or Nominal Watt	13W

