

120V LED 12.5W 35 Deg FL 30K AZT
16201AZT30 (Textured Architectural Bronze)

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Dimensions

| | |
|--------|-------|
| Height | 4.75" |
| Length | 4.75" |
| Width | 3.00" |

Ordering Information

| | |
|--------------------|-------------------------------|
| Product ID | 16201AZT30 |
| Finish | Textured Architectural Bronze |
| Available Finishes | AZT, AZT, BBR, BBR, WHT, WHT |

Dimensions

| | |
|--------|----------|
| Weight | 1.15 LBS |
|--------|----------|

Photometrics

| | |
|-----------------------|-------|
| Kelvin Temperature | 3000K |
| Color Rendering Index | 80 |

Specifications

| | |
|-------------------|----------------------|
| Material | Aluminum |
| Glass Description | 35 Beam Spread Optic |

Electrical

| | |
|-------------------------|-------------|
| Voltage | 120VAC |
| Operating Voltage Range | 108-132 VAC |

Qualifications

| | |
|--------------------|--------------------------|
| Safety Rated | Wet |
| Expected Life Span | 40000 Hours |
| Warranty | www.kichler.com/warranty |

Primary Lamping

| | |
|-----------------------|------------|
| Light Source | LED |
| Lamp Included | Integrated |
| Number of Lights/LEDs | 5 |
| Max or Nominal Watt | 12.5W |

120V LED 12.5W 35 Deg FL 42K AZT
16201AZT42 (Textured Architectural Bronze)

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Dimensions

| | |
|--------|-------|
| Height | 4.75" |
| Length | 4.75" |
| Width | 3.00" |

Ordering Information

| | |
|--------------------|-------------------------------|
| Product ID | 16201AZT42 |
| Finish | Textured Architectural Bronze |
| Available Finishes | AZT, AZT, BBR, BBR, WHT, WHT |

Dimensions

| | |
|--------|----------|
| Weight | 1.15 LBS |
|--------|----------|

Photometrics

| | |
|-----------------------|-------|
| Kelvin Temperature | 4250K |
| Color Rendering Index | 75 |

Specifications

| | |
|-------------------|----------------------|
| Material | Aluminum |
| Glass Description | 35 Beam Spread Optic |

Electrical

| | |
|-------------------------|-------------|
| Voltage | 120VAC |
| Operating Voltage Range | 108-132 VAC |

Qualifications

| | |
|--------------------|--------------------------|
| Safety Rated | Wet |
| Expected Life Span | 40000 Hours |
| Warranty | www.kichler.com/warranty |

Primary Lamping

| | |
|-----------------------|------------|
| Light Source | LED |
| Lamp Included | Integrated |
| Number of Lights/LEDs | 5 |
| Max or Nominal Watt | 12.5W |

120V LED 12.5W 35 Deg FL 30K BBR
16201BBR30 (Bronzed Brass)

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Dimensions

| | |
|--------|-------|
| Height | 4.75" |
| Length | 4.75" |
| Width | 3.00" |

Ordering Information

| | |
|--------------------|------------------------------|
| Product ID | 16201BBR30 |
| Finish | Bronzed Brass |
| Available Finishes | AZT, AZT, BBR, BBR, WHT, WHT |

Dimensions

| | |
|--------|----------|
| Weight | 1.15 LBS |
|--------|----------|

Photometrics

| | |
|-----------------------|-------|
| Kelvin Temperature | 3000K |
| Color Rendering Index | 80 |

Specifications

| | |
|-------------------|----------------------|
| Material | Brass |
| Glass Description | 35 Beam Spread Optic |

Electrical

| | |
|-------------------------|-------------|
| Voltage | 120VAC |
| Operating Voltage Range | 108-132 VAC |

Qualifications

| | |
|--------------------|--------------------------|
| Safety Rated | Wet |
| Expected Life Span | 40000 Hours |
| Warranty | www.kichler.com/warranty |

Primary Lamping

| | |
|-----------------------|------------|
| Light Source | LED |
| Lamp Included | Integrated |
| Number of Lights/LEDs | 5 |
| Max or Nominal Watt | 12.5W |

120V LED 12.5W 35 Deg FL 42K BBR
16201BBR42 (Bronzed Brass)

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Dimensions

| | |
|--------|-------|
| Height | 4.75" |
| Length | 4.75" |
| Width | 3.00" |

Ordering Information

| | |
|--------------------|------------------------------|
| Product ID | 16201BBR42 |
| Finish | Bronzed Brass |
| Available Finishes | AZT, AZT, BBR, BBR, WHT, WHT |

Dimensions

| | |
|--------|----------|
| Weight | 1.15 LBS |
|--------|----------|

Photometrics

| | |
|-----------------------|-------|
| Kelvin Temperature | 4250K |
| Color Rendering Index | 75 |

Specifications

| | |
|-------------------|----------------------|
| Material | Brass |
| Glass Description | 35 Beam Spread Optic |

Electrical

| | |
|-------------------------|-------------|
| Voltage | 120VAC |
| Operating Voltage Range | 108-132 VAC |

Qualifications

| | |
|--------------------|--------------------------|
| Safety Rated | Wet |
| Expected Life Span | 40000 Hours |
| Warranty | www.kichler.com/warranty |

Primary Lamping

| | |
|-----------------------|------------|
| Light Source | LED |
| Lamp Included | Integrated |
| Number of Lights/LEDs | 5 |
| Max or Nominal Watt | 12.5W |

120V LED 12.5W 35 Deg FL 3000K
16201WHT30 (Textured White)

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Dimensions

| | |
|--------|-------|
| Height | 4.75" |
| Length | 4.75" |
| Width | 3.00" |

Ordering Information

| | |
|--------------------|------------------------------|
| Product ID | 16201WHT30 |
| Finish | Textured White |
| Available Finishes | AZT, AZT, BBR, BBR, WHT, WHT |

Dimensions

| | |
|--------|----------|
| Weight | 1.15 LBS |
|--------|----------|

Photometrics

| | |
|-----------------------|-------|
| Kelvin Temperature | 3000K |
| Color Rendering Index | 80 |

Specifications

| | |
|-------------------|----------------------|
| Material | Aluminum |
| Glass Description | 35 Beam Spread Optic |

Electrical

| | |
|-------------------------|-------------|
| Voltage | 120VAC |
| Operating Voltage Range | 108-132 VAC |

Qualifications

| | |
|--------------------|--------------------------|
| Safety Rated | Wet |
| Expected Life Span | 40000 Hours |
| Warranty | www.kichler.com/warranty |

Primary Lamping

| | |
|-----------------------|------------|
| Light Source | LED |
| Lamp Included | Integrated |
| Number of Lights/LEDs | 5 |
| Max or Nominal Watt | 12.5W |

120V LED 12.5W 35 Deg FL 4250K
16201WHT42 (Textured White)

Project Name: _____
Location: _____
Type: _____
Qty: _____
Comments: _____



Dimensions

| | |
|--------|-------|
| Height | 4.75" |
| Length | 4.75" |
| Width | 3.00" |

Ordering Information

| | |
|--------------------|------------------------------|
| Product ID | 16201WHT42 |
| Finish | Textured White |
| Available Finishes | AZT, AZT, BBR, BBR, WHT, WHT |

Dimensions

| | |
|--------|----------|
| Weight | 1.15 LBS |
|--------|----------|

Photometrics

| | |
|-----------------------|-------|
| Kelvin Temperature | 4250K |
| Color Rendering Index | 75 |

Specifications

| | |
|-------------------|----------------------|
| Material | Aluminum |
| Glass Description | 35 Beam Spread Optic |

Electrical

| | |
|-------------------------|-------------|
| Voltage | 120VAC |
| Operating Voltage Range | 108-132 VAC |

Qualifications

| | |
|--------------------|--------------------------|
| Safety Rated | Wet |
| Expected Life Span | 40000 Hours |
| Warranty | www.kichler.com/warranty |

Primary Lamping

| | |
|-----------------------|------------|
| Light Source | LED |
| Lamp Included | Integrated |
| Number of Lights/LEDs | 5 |
| Max or Nominal Watt | 12.5W |