

29W 120V 60 DEG 3000K Aluminum  
16208AZT30 (Textured Architectural Bronze)

Project Name: \_\_\_\_\_  
Location: \_\_\_\_\_  
Type: \_\_\_\_\_  
Qty: \_\_\_\_\_  
Comments: \_\_\_\_\_



Dimensions

|        |       |
|--------|-------|
| Height | 5.50" |
| Length | 6.50" |
| Width  | 4.50" |

Ordering Information

|                    |                               |
|--------------------|-------------------------------|
| Product ID         | 16208AZT30                    |
| Finish             | Textured Architectural Bronze |
| Available Finishes | BBR, BBR, AZT, AZT, WHT, WHT  |

Dimensions

|        |          |
|--------|----------|
| Weight | 2.00 LBS |
|--------|----------|

Photometrics

|                       |       |
|-----------------------|-------|
| Kelvin Temperature    | 3000K |
| Color Rendering Index | 80    |

Specifications

|                   |                      |
|-------------------|----------------------|
| Material          | Aluminum             |
| Glass Description | 60 Beam Spread Optic |

Electrical

|                         |             |
|-------------------------|-------------|
| Voltage                 | 120VAC      |
| Operating Voltage Range | 108-132 VAC |

Qualifications

|                    |                                                                        |
|--------------------|------------------------------------------------------------------------|
| Safety Rated       | Wet                                                                    |
| Expected Life Span | 40000 Hours                                                            |
| Warranty           | <a href="http://www.kichler.com/warranty">www.kichler.com/warranty</a> |

Primary Lamping

|                       |            |
|-----------------------|------------|
| Light Source          | LED        |
| Lamp Included         | Integrated |
| Number of Lights/LEDs | 8          |
| Max or Nominal Watt   | 29W        |

29W 120V 60 DEG 3000K Aluminum  
16208WHT30 (Textured White)

Project Name: \_\_\_\_\_  
Location: \_\_\_\_\_  
Type: \_\_\_\_\_  
Qty: \_\_\_\_\_  
Comments: \_\_\_\_\_



Dimensions

|        |       |
|--------|-------|
| Height | 5.50" |
| Length | 6.50" |
| Width  | 4.50" |

Ordering Information

|                    |                              |
|--------------------|------------------------------|
| Product ID         | 16208WHT30                   |
| Finish             | Textured White               |
| Available Finishes | BBR, BBR, AZT, AZT, WHT, WHT |

Dimensions

|        |          |
|--------|----------|
| Weight | 2.00 LBS |
|--------|----------|

Photometrics

|                       |       |
|-----------------------|-------|
| Kelvin Temperature    | 3000K |
| Color Rendering Index | 80    |

Specifications

|                   |                      |
|-------------------|----------------------|
| Material          | Aluminum             |
| Glass Description | 60 Beam Spread Optic |

Electrical

|                         |             |
|-------------------------|-------------|
| Voltage                 | 120VAC      |
| Operating Voltage Range | 108-132 VAC |

Qualifications

|                    |                          |
|--------------------|--------------------------|
| Safety Rated       | Wet                      |
| Expected Life Span | 40000 Hours              |
| Warranty           | www.kichler.com/warranty |

Primary Lamping

|                       |            |
|-----------------------|------------|
| Light Source          | LED        |
| Lamp Included         | Integrated |
| Number of Lights/LEDs | 8          |
| Max or Nominal Watt   | 29W        |

29W 120V 60 DEG 4250K Aluminum  
16208AZT42 (Textured Architectural Bronze)

Project Name: \_\_\_\_\_  
Location: \_\_\_\_\_  
Type: \_\_\_\_\_  
Qty: \_\_\_\_\_  
Comments: \_\_\_\_\_



Dimensions

|        |       |
|--------|-------|
| Height | 5.50" |
| Length | 6.50" |
| Width  | 4.50" |

Ordering Information

|                    |                               |
|--------------------|-------------------------------|
| Product ID         | 16208AZT42                    |
| Finish             | Textured Architectural Bronze |
| Available Finishes | BBR, BBR, AZT, AZT, WHT, WHT  |

Dimensions

|        |          |
|--------|----------|
| Weight | 2.00 LBS |
|--------|----------|

Photometrics

|                       |       |
|-----------------------|-------|
| Kelvin Temperature    | 4250K |
| Color Rendering Index | 75    |

Specifications

|                   |                      |
|-------------------|----------------------|
| Material          | Aluminum             |
| Glass Description | 60 Beam Spread Optic |

Electrical

|                         |             |
|-------------------------|-------------|
| Voltage                 | 120VAC      |
| Operating Voltage Range | 108-132 VAC |

Qualifications

|                    |                          |
|--------------------|--------------------------|
| Safety Rated       | Wet                      |
| Expected Life Span | 40000 Hours              |
| Warranty           | www.kichler.com/warranty |

Primary Lamping

|                       |            |
|-----------------------|------------|
| Light Source          | LED        |
| Lamp Included         | Integrated |
| Number of Lights/LEDs | 8          |
| Max or Nominal Watt   | 29W        |

29W 120V 60 DEG 4250K Aluminum  
16208WHT42 (Textured White)

Project Name: \_\_\_\_\_  
Location: \_\_\_\_\_  
Type: \_\_\_\_\_  
Qty: \_\_\_\_\_  
Comments: \_\_\_\_\_



Dimensions

|        |       |
|--------|-------|
| Height | 5.50" |
| Length | 6.50" |
| Width  | 4.50" |

Ordering Information

|                    |                              |
|--------------------|------------------------------|
| Product ID         | 16208WHT42                   |
| Finish             | Textured White               |
| Available Finishes | BBR, BBR, AZT, AZT, WHT, WHT |

Dimensions

|        |          |
|--------|----------|
| Weight | 2.00 LBS |
|--------|----------|

Photometrics

|                       |       |
|-----------------------|-------|
| Kelvin Temperature    | 4250K |
| Color Rendering Index | 75    |

Specifications

|                   |                      |
|-------------------|----------------------|
| Material          | Aluminum             |
| Glass Description | 60 Beam Spread Optic |

Electrical

|                         |             |
|-------------------------|-------------|
| Voltage                 | 120VAC      |
| Operating Voltage Range | 108-132 VAC |

Qualifications

|                    |                                                                        |
|--------------------|------------------------------------------------------------------------|
| Safety Rated       | Wet                                                                    |
| Expected Life Span | 40000 Hours                                                            |
| Warranty           | <a href="http://www.kichler.com/warranty">www.kichler.com/warranty</a> |

Primary Lamping

|                       |            |
|-----------------------|------------|
| Light Source          | LED        |
| Lamp Included         | Integrated |
| Number of Lights/LEDs | 8          |
| Max or Nominal Watt   | 29W        |

29W 120V 60 DEG 3000K Brass  
16208BBR30 (Bronzed Brass)

Project Name: \_\_\_\_\_  
Location: \_\_\_\_\_  
Type: \_\_\_\_\_  
Qty: \_\_\_\_\_  
Comments: \_\_\_\_\_



Dimensions

|        |       |
|--------|-------|
| Height | 5.50" |
| Length | 6.50" |
| Width  | 4.50" |

Ordering Information

|                    |                              |
|--------------------|------------------------------|
| Product ID         | 16208BBR30                   |
| Finish             | Bronzed Brass                |
| Available Finishes | AZT, AZT, BBR, BBR, WHT, WHT |

Dimensions

|        |          |
|--------|----------|
| Weight | 2.00 LBS |
|--------|----------|

Photometrics

|                       |       |
|-----------------------|-------|
| Kelvin Temperature    | 3000K |
| Color Rendering Index | 80    |

Specifications

|                   |                      |
|-------------------|----------------------|
| Material          | Brass                |
| Glass Description | 60 Beam Spread Optic |

Electrical

|                         |             |
|-------------------------|-------------|
| Voltage                 | 120VAC      |
| Operating Voltage Range | 108-132 VAC |

Qualifications

|                    |                          |
|--------------------|--------------------------|
| Safety Rated       | Wet                      |
| Expected Life Span | 40000 Hours              |
| Warranty           | www.kichler.com/warranty |

Primary Lamping

|                       |            |
|-----------------------|------------|
| Light Source          | LED        |
| Lamp Included         | Integrated |
| Number of Lights/LEDs | 8          |
| Max or Nominal Watt   | 29W        |

29W 120V 60 DEG 4250K Brass  
16208BBR42 (Bronzed Brass)

Project Name: \_\_\_\_\_  
Location: \_\_\_\_\_  
Type: \_\_\_\_\_  
Qty: \_\_\_\_\_  
Comments: \_\_\_\_\_



Dimensions

|        |       |
|--------|-------|
| Height | 5.50" |
| Length | 6.50" |
| Width  | 4.50" |

Ordering Information

|                    |                              |
|--------------------|------------------------------|
| Product ID         | 16208BBR42                   |
| Finish             | Bronzed Brass                |
| Available Finishes | BBR, BBR, AZT, AZT, WHT, WHT |

Dimensions

|        |          |
|--------|----------|
| Weight | 2.00 LBS |
|--------|----------|

Photometrics

|                       |       |
|-----------------------|-------|
| Kelvin Temperature    | 4250K |
| Color Rendering Index | 75    |

Specifications

|                   |                      |
|-------------------|----------------------|
| Material          | Brass                |
| Glass Description | 60 Beam Spread Optic |

Electrical

|                         |             |
|-------------------------|-------------|
| Voltage                 | 120VAC      |
| Operating Voltage Range | 108-132 VAC |

Qualifications

|                    |                          |
|--------------------|--------------------------|
| Safety Rated       | Wet                      |
| Expected Life Span | 40000 Hours              |
| Warranty           | www.kichler.com/warranty |

Primary Lamping

|                       |            |
|-----------------------|------------|
| Light Source          | LED        |
| Lamp Included         | Integrated |
| Number of Lights/LEDs | 8          |
| Max or Nominal Watt   | 29W        |