
Sutter Place Premier Collectio 52 Inch Sutter Place Premier Fan AP

339400AP (Antique Pewter)



Dimensions



Downrod	Α	В	С	D
1.00 OD X 4.00	18.75	10.75	12.00	5.25
FLUSH MOUNT	15.25	8.00	12.00	5.25

Available Finishes

Finish	Fixture	Glass	Blade 1	Blade 2	
--------	---------	-------	---------	---------	--

Project Name:	
Location:	
Туре:	
Qty:	
Comments:	

Product Information

Product ID	339400AP
Finish	Antique Pewter
Blade Finish	Light Cherry/Black Cherry
Collection	Sutter Place Premier Collectio

Airflow, Power and Efficiency

Speed	RPM	CFM	CFM/ Watt	Amps	Watts
High	160	4500	76	.49	59
Med	113	3196	114	.35	28
Low	62	1602	169	.2	10

Specifications

opedifications	
Number of Blades	5
Blades Included	Yes
Blade Pitch	12 Degrees
Blade Sweep	52"
Blades Reversible	Yes
Blade Material	WOOD
Optional Blades Available	No
Downrod 1	1.00 OD X 4.00
Downrod 2	FLUSH MOUNT
Primary Control System	Pull Chain
Remote Included	No
Wall Control Included	No
Low Ceiling Adaptable	Yes, Dual Mount Included
Lead Wire Length	78.00"
Motor Size	153MM X 15MM
Motor Type	AC

Downlight

Downlight Included	Yes
Light Source	Incandescent
Downlight Bulb Included	Included
Downlight Bulb Type	B10
Number of Lights/LEDs	3
Max or Nominal Watt	60W
Glass Description	Satin Etched
Optional Light Kit Available	No

Safety Listings & Certifications



7711 East Pleasant Valley Road Cleveland, Ohio 44131-8010 Toll free: 866.558.5706 or kichler.com

Notes

Information provided is subject to change without notice.

All values are design or typical values when measured under laboratory conditions.

Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.



Sutter Place Premier Collectio 52 Inch Sutter Place Premier Fan AP

339400AP (Antique Pewter)

Antique Pewter	339400AP	SATIN ETCHED	LIGHT CHERRY	BLACK CHERRY
Oil Brushed Bronze	339400OBB	UMBER ALABASTER	WALNUT	CHERRY
Olde Bronze	339400OZ	UMBER ALABASTER	WALNUT	CHERRY
Matte White	339400MWH	WHITE ALABASTER	MATTE WHITE	MATTE WHITE

Control Options

Product ID	Descr
337001WH	Universal Remote Control
337010ALM	Fan 4 Speed-Light Dimmer
337010IV	Fan 4 Speed-Light Dimmer
337010WH	Fan 4 Speed-Light Dimmer
337011ALM	Fan Light Dimmer Control
337011IV	Fan Light Dimmer Control
337011WH	Fan Light Dimmer Control
337012ALM	4 Speed Fan Slide Control
337012IV	4 Speed Fan Slide Control
337012WH	4 Speed Fan Slide Control
337214	Limited Function Cooltouch
370039MUL	Wall Control System L-Function
371042MUL	56K Wall Control System Basic


Dry
Dry
Dry
Dry
www.kichler.com/warranty
The electrical junction box and support structure must be securely mounted and capable of reliably supporting a minimum of 50 pounds. Use only ETL/UL listed electrical junction boxes marked ""For Fan Support""
120V 60Hz AC
20 LBS
7.5 feet

Sutter Place Premier Collectio 52" Sutter Place Premier Fan MWH

339400MWH



Dimensions



Downrod	Α	В	С	D
1.00 OD X 4.00	18.75	10.75	12.00	5.25
FLUSH MOUNT	15.25	8.00	12.00	5.25

Available Finishes

Finish	Fixture	Glass	Blade 1	Blade 2	

Project Name:	
Location:	
Туре:	
Qty:	
Comments:	

Product Information

Product ID	339400MWH
Blade Finish	Matte White/Matte White
Collection	Sutter Place Premier Collectio

Airflow, Power and Efficiency

Speed	RPM	CFM	CFM/ Watt	Amps	Watts
High	160	4500	76	.49	59
Med	113	3196	114	.35	28
Low	62	1602	169	.2	10

Specifications

Opecinications	
Number of Blades	5
Blades Included	Yes
Blade Pitch	12 Degrees
Blade Sweep	52"
Blades Reversible	Yes
Blade Material	WOOD
Optional Blades Available	No
Downrod 1	1.00 OD X 4.00
Downrod 2	FLUSH MOUNT
Primary Control System	Pull Chain
Remote Included	No
Wall Control Included	No
Low Ceiling Adaptable	Yes, Dual Mount Included
Motor Size	153MM X 15MM
Motor Type	AC

Downlight

Downlight Included	Yes
Light Source	Incandescent
Downlight Bulb Included	Included
Downlight Bulb Type	B10
Number of Lights/LEDs	3
Max or Nominal Watt	60W
Glass Description	Alabaster Swirl
Optional Light Kit Available	No

Safety Listings & Certifications

Safety Rated	Dry
Warranty	www.kichler.com/warranty



7711 East Pleasant Valley Road Cleveland, Ohio 44131-8010 Toll free: 866.558.5706 or kichler.com

Notes

Information provided is subject to change without notice.

All values are design or typical values when measured under laboratory conditions.

Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.



Sutter Place Premier Collectio 52" Sutter Place Premier Fan MWH

339400MWH

Antique Pewter	339400AP	SATIN ETCHED	LIGHT CHERRY	BLACK CHERRY
Oil Brushed Bronze	339400OBB	UMBER ALABASTER	WALNUT	CHERRY
Olde Bronze	339400OZ	UMBER ALABASTER	WALNUT	CHERRY
Matte White	339400MWH	WHITE ALABASTER	MATTE WHITE	MATTE WHITE

O 4 1	O 11
(:nntrn	l Options
COLITIO	Options

Product ID	Descr
337001WH	Universal Remote Control
337010ALM	Fan 4 Speed-Light Dimmer
337010IV	Fan 4 Speed-Light Dimmer
337010WH	Fan 4 Speed-Light Dimmer
337011ALM	Fan Light Dimmer Control
337011IV	Fan Light Dimmer Control
337011WH	Fan Light Dimmer Control
337012ALM	4 Speed Fan Slide Control
337012IV	4 Speed Fan Slide Control
337012WH	4 Speed Fan Slide Control
337214	Limited Function Cooltouch
370039MUL	Wall Control System L-Function
371042MUL	56K Wall Control System Basic

Project Name:
_ocation:
Гуре:
Qty:
Comments:


The electrical junction box and support structure must be securely mounted and capable of reliably supporting a minimum of 50 pounds. Use only ETL/UL listed electrical junction boxes marked ""For Fan Support""
120V 60Hz AC
20 LBS
7.5 feet

Sutter Place Premier Collectio 52 Inch Sutter Place Premier Fan OBB

339400OBB (Oil Brushed Bronze)



Dimensions



Downrod	Α	В	С	D
1.00 OD X 4.00	18.75	10.75	12.00	5.25
FLUSH MOUNT	15.25	8.00	12.00	5.25

Available Finishes

Finish	Fixture	Glass	Blade 1	Blade 2	

Project Name:	
Location:	
Туре:	
Qty:	
Comments:	

Product Information

Product ID	339400OBB
Finish	Oil Brushed Bronze
Blade Finish	Walnut/Cherry
Collection	Sutter Place Premier Collectio

Airflow, Power and Efficiency

Speed	RPM	CFM	CFM/ Watt	Amps	Watts
High	160	4500	76	.49	59
Med	113	3196	114	.35	28
Low	62	1602	169	.2	10

Specifications

Opcomodiono	
Number of Blades	5
Blades Included	Yes
Blade Pitch	12 Degrees
Blade Sweep	52"
Blades Reversible	Yes
Blade Material	WOOD
Optional Blades Available	No
Downrod 1	1.00 OD X 4.00
Downrod 2	FLUSH MOUNT
Primary Control System	Pull Chain
Remote Included	No
Wall Control Included	No
Low Ceiling Adaptable	Yes, Dual Mount Included
Lead Wire Length	78.00"
Motor Size	153MM X 15MM
Motor Type	AC

Downlight

Downlight Included	Yes
Light Source	Incandescent
Downlight Bulb Included	Included
Downlight Bulb Type	B10
Number of Lights/LEDs	3
Max or Nominal Watt	60W
Glass Description	Umber Alabaster
Optional Light Kit Available	No

Safety Listings & Certifications



7711 East Pleasant Valley Road Cleveland, Ohio 44131-8010 Toll free: 866.558.5706 or kichler.com

Notes

Information provided is subject to change without notice.

All values are design or typical values when measured under laboratory conditions.

2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.



Sutter Place Premier Collectio 52 Inch Sutter Place Premier Fan OBB

339400OBB (Oil Brushed Bronze)

Antique Pewter	339400AP	SATIN ETCHED	LIGHT CHERRY	BLACK CHERRY
Oil Brushed Bronze	339400OBB	UMBER ALABASTER	WALNUT	CHERRY
Olde Bronze	339400OZ UMBER ALABASTER		WALNUT	CHERRY
Matte White	339400MWH	WHITE ALABASTER	MATTE WHITE	MATTE WHITE

Control Options

Product ID	Descr
337001WH	Universal Remote Control
337010ALM	Fan 4 Speed-Light Dimmer
337010IV	Fan 4 Speed-Light Dimmer
337010WH	Fan 4 Speed-Light Dimmer
337011ALM	Fan Light Dimmer Control
337011IV	Fan Light Dimmer Control
337011WH	Fan Light Dimmer Control
337012ALM	4 Speed Fan Slide Control
337012IV	4 Speed Fan Slide Control
337012WH	4 Speed Fan Slide Control
337214	Limited Function Cooltouch
370039MUL	Wall Control System L-Function
371042MUL	56K Wall Control System Basic


Project Name:	
Location:	
Туре:	
Qty:	
Comments:	
Safety Rated	Dry
Warranty	www.kichler.com/warranty
Installation	
Installation requirements	The electrical junction box and support structure must be securely mounted and capable of reliably supporting a minimum of 50 pounds. Use only ETL/UL listed electrical junction boxes marked ""For Fan Support""
Electrical Requirements	120V 60Hz AC
Hanging Weight	20 LBS
Minimum Distance Between Bottom Of Fan Blade To Floor	7.5 feet

Sutter Place Premier Collectio 52 Inch Sutter Place Premier F OZ

339400OZ (Olde Bronze)



Dimensions



Downrod	Α	В	С	D
1.00 OD X 4.00	18.75	10.75	12.00	5.25
FLUSH MOUNT	15.00	8.00	12.00	5.25

Available Finishes

Finish	Fixture	Glass	Blade 1	Blade 2
--------	---------	-------	---------	---------

Project Name:
ocation:
ype:
Ωty:
Comments:

Product Information

Product ID	339400OZ
Finish	Olde Bronze
Blade Finish	Walnut/Cherry
Collection	Sutter Place Premier Collectio

Airflow, Power and Efficiency

Speed	RPM	CFM	CFM/ Watt	Amps	Watts
High	160	4500	76	.49	59
Med	113	3196	114	.35	28
Low	62	1602	169	.2	10

Specifications

оросиновно	
Number of Blades	5
Blades Included	Yes
Blade Pitch	12 Degrees
Blade Sweep	52"
Blades Reversible	Yes
Blade Material	WOOD
Optional Blades Available	No
Downrod 1	1.00 OD X 4.00
Downrod 2	FLUSH MOUNT
Primary Control System	Pull Chain
Remote Included	No
Wall Control Included	No
Low Ceiling Adaptable	Yes, Dual Mount Included
Lead Wire Length	78.00"
Motor Size	153MM X 15MM
Motor Type	AC

Downlight

Downlight Included	Yes
Light Source	Incandescent
Downlight Bulb Included	Included
Downlight Bulb Type	B10
Number of Lights/LEDs	3
Max or Nominal Watt	60W
Glass Description	Umber Alabaster
Optional Light Kit Available	No

Safety Listings & Certifications



7711 East Pleasant Valley Road Cleveland, Ohio 44131-8010 Toll free: 866.558.5706 or kichler.com

Notes

Information provided is subject to change without notice.

All values are design or typical values when measured under laboratory conditions.

Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.



Sutter Place Premier Collectio 52 Inch Sutter Place Premier F OZ

339400OZ (Olde Bronze)

Antique Pewter	339400AP	SATIN ETCHED	LIGHT CHERRY	BLACK CHERRY
Oil Brushed Bronze	339400OBB	UMBER ALABASTER	WALNUT	CHERRY
Olde Bronze	339400OZ	UMBER ALABASTER	WALNUT	CHERRY
Matte White	339400MWH	WHITE ALABASTER	MATTE WHITE	MATTE WHITE

Control Options

Product ID	Descr
337001WH	Universal Remote Control
337010ALM	Fan 4 Speed-Light Dimmer
337010IV	Fan 4 Speed-Light Dimmer
337010WH	Fan 4 Speed-Light Dimmer
337011ALM	Fan Light Dimmer Control
337011IV	Fan Light Dimmer Control
337011WH	Fan Light Dimmer Control
337012ALM	4 Speed Fan Slide Control
337012IV	4 Speed Fan Slide Control
337012WH	4 Speed Fan Slide Control
337214	Limited Function Cooltouch
370039MUL	Wall Control System L-Function
371042MUL	56K Wall Control System Basic

Project Name: Location: Type: Qty: Comments:	
Safety Rated	Dry
Warranty	www.kichler.com/warranty
Installation	
Installation requirements	The electrical junction box and support structure must be securely mounted and capable of reliably supporting a minimum of 50 pounds. Use only ETL/UL listed electrical junction boxes marked ""For Fan Support""
Electrical Requirements	120V 60Hz AC
Hanging Weight	20 LBS
Minimum Distance Between Bottom Of Fan Blade To Floor	7.5 feet