MINTA TOUCH Pull-Down kitchen faucet with touch technology


MODEL # 30218000





GROHE America, Inc | 200 North Gary Avenue, Suite G, Roselle, IL 60172 Phone: +1 (800) 444-7643 | Fax: +1 (800) 225-2778 | us-customerservice@grohe.com











Product Description:

Pull-Down kitchen faucet with touch technology

Standard Specification:

- Single hole installation
- Touch: activation of cold water via skin contact
- 6 V lithium-battery supply (type CR-P2)
- CE approved
- Indication of battery status through different pulses of water
- Safety shut down circuit (when battery nearly empty)
- Solenoid valve
- Automatic safety stop after 60 sec. (factory set)
- Type of protection IP 44
- GROHE SilkMove ceramic cartridge
- GROHE StarLight finish
- GROHE SuperSteel Infinity Finish™
- L-spout
- Adjustable flow rate limiter
- Swivel Spout
- Swivel area 360°
- Single Spray Pull-Out
- Integrated non-return valve
- Automatic returning
- Stainless steel flex lines
- Quick installation system
- Protected against backflow

Applicable Codes & Standards:

- Energy Policy Act of 1992
- NSF 61
- ASME A112.18.1/CSA B125.1
- US Federal and State material regulations
- ICC/ANSI A117.1

Color:

□ 30218000 000 chrome

MINTA TOUCH Pull-Down kitchen faucet with touch technology


MODEL # 30218DC0

Pure Freude an Wasser



GROHE America, Inc | 200 North Gary Avenue, Suite G, Roselle, IL 60172 Phone: +1 (800) 444-7643 | Fax: +1 (800) 225-2778 | us-customerservice@grohe.com











Product Description:

Pull-Down kitchen faucet with touch technology

Standard Specification:

- Single hole installation
- Touch: activation of cold water via skin contact
- 6 V lithium-battery supply (type CR-P2)
- CE approved
- Indication of battery status through different pulses of water
- Solenoid valve
- Safety shut down circuit (when battery nearly empty)
- Automatic safety stop after 60 sec. (factory set)
- Type of protection IP 44
- GROHE SilkMove ceramic cartridge
- GROHE StarLight finish
- GROHE SuperSteel Infinity Finish™
- L-spout
- Swivel Spout
- Adjustable flow rate limiter
- Swivel area 360°
- Single Spray Pull-Out
- Automatic returning
- Integrated non-return valve
- Stainless steel flex lines
- Quick installation system
- Protected against backflow

Applicable Codes & Standards:

- Energy Policy Act of 1992
- NSF 61
- ASME A112.18.1/CSA B125.1
- US Federal and State material regulations
- ICC/ANSI A117.1

Color:

□ 30218DC0 DC0 supersteel